

Product datasheet

Specifications



mini Pragma recessed enclosure - 1 x 18 modules - plain door

MIP22118

Main

| | |
|-----------------------------|---|
| Range | Resi9 |
| Product name | Resi9 MP |
| Product or component type | Enclosure |
| Enclosure type | Modular enclosure |
| Nb of 18 mm modules per row | 18 |
| Nb of horizontal rows | 1 |
| Type of door | Plain |
| Width | 378 mm wall: 402 mm outside: |
| Height | 228 mm wall: 252 mm outside: |
| Depth | 18 mm outside: 80 mm wall: 98 mm total: |

Complementary

| | |
|-------------------------------|--|
| Enclosure mounting | Flush |
| 9 mm pitches | 36 |
| Total number of 18 mm modules | 18 |
| [In] rated current | 63 A |
| Type of rail | 35 mm asymmetrical rail |
| Mounting plate description | Without mounting plate |
| Cable entry | Pre-cutted holes |
| Terminal block function | Earth / neutral |
| Number of terminal blocks | 1 earth (screwed) with 16 outgoing 1 neutral (screwed) with 16 outgoing |
| Distribution block outgoing | 2 x 16 mm ² for earth 2 x 16 mm ² for neutral 6 x 6 mm ² for earth 6 x 6 mm ² for neutral 8 x 10 mm ² for earth 8 x 10 mm ² for neutral |
| Enclosure material | Back part: technoplastic Door: technoplastic Front face: technoplastic |
| Internal depth | 76 mm |

| | |
|--|---|
| Colour | Door: white (RAL 9003) Front face: white (RAL 9003) |
| Market segment | Small commercial Residential |
| Environment | |
| Standards | IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24 |
| Quality labels | IMQ |
| Fire resistance | Door: 650 °C Back part: 650 °C Front face: 650 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | -25...60 °C |
| Packing Units | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 9.900 cm |
| Package 1 Width | 40.200 cm |
| Package 1 Length | 25.200 cm |
| Package 1 Weight | 1.200 kg |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 5 |
| Package 2 Height | 52.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 6.900 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 80 |
| Package 3 Height | 120.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 97.600 kg |
| Offer Sustainability | |
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Halogen content performance Halogen free product

Contractual warranty

Warranty 12 months

Recommended replacement(s)